


### STANDARD FEATURES

- Heavy-duty design
- 60° cone
- Smooth interior
- Manway or handway
- Butterfly valve with pneumatic actuator
- Rotable outlet
- Erosion allowances on wear surface

### OPTIONAL FEATURES

- Aeration jets
- Interior coatings / Finishing
- Multiple inlets
- Stainless construction AISI 304/316
- Higher pressure and temperature ratings
- ATEX design 94/9/CE 
- Electronic multi pressure control
- Customized inlet valve sizes

### SPECIFICATIONS

- Design pressure: 6 bar
- Temperature range: -10C° a +50C°
- PED 97/23/CE

### TRANSPORTER

Model No.	Capacity [Lt]	A [mm]	B [mm]	Ø Dia. [mm]	Inlet Valve DN	Ship Wt. [Kg]
PP0024	24	865	1071	600	150	73
PP0070	70	1130	1335	800	150	82
PP0102	102	1170	1349	810	150	95
PP0140	140	1370	1576	810	150	110
PP0280	280	1608	1820	1010	200	160
PP0346	346	1788	1838	1115	200	292
PP0490	490	1938	2088	1115	200	300
PP0600	600	1905	2165	1253	200	332
PP0850	850	2190	2450	1253	200	350
PP1100	1100	2591	2851	1253	200	455
PP1700	1700	2743	3061	1605	250	640
PP2200	2200	3200	3518	1605	250	825
PP2800	2800	3582	3900	1605	250	1050
PP4200	4200	3734	4112	2060	300	1240
PP5600	5600	4267	4645	2060	300	1480
PP7000	7000	4800	5176	2060	300	2255
PP14000	14000	5715	6090	2440	300	3970
PP21200	21200	6175	6550	3050	300	4540
PP28000	28000	7165	7540	3050	300	5215

THE **NOL-TEC** TRANSPORTERS ARE DESIGNED TO PROVIDE TROUBLE-FREE DENSE PHASE PNEUMATIC CONVEYING OF MOST MATERIALS.