


DN	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]
2"	975	152	248	165	148	102	1291
3"	1197	178	305	203	152	114	1511
4"	1397	203	357	250	133	114	1835
5"	1505	229	394	250	133	127	1950
6"	1673	254	444.5	292	132	140	2206

STANDARD FEATURES

- Heavy-duty, carbon steel construction;
- Stainless seal and slide plates;
- Single air cylinder positioning;
- Abrasion resistant rubber hose;
- Conveying pressure to 5 bar;
- Pressure or vacuum capabilities;
- Suitable for converging or diverging applications;
- Urethane sealing rings;
- Unused port blocked;
- Switches to indicate position;
- Tabs for tie bars;
- Clean wipe seal controls.

OPTIONAL FEATURES

- Stainless product contact;
- Stainless construction;
- ATEX design 94/9/CE; 
- FDA white rubber hose;
- Hose support frame;
- High temperature;
- Contact NOL-TEC with your requirements.

SPECIFICATIONS

- Air:
 - Clean and dry at correct pressure dew point;
 - 6,5 bar minimum.
- Electrical: 24 Vdc.
- Temperature:
 - Continuous: 65 °C;
 - Intermittent: 80 °C.